

EMJ-10 Series Servo Motor

FEATURES

- **Medium Inertia**
- **Rated Torque of 450 oz-in**
- **Peak Torque up to 300% of Rated Torque**
- **Peak Current up to 300% of Rated Current**
- **Speed of up to 4,500 RPM**
- **2,500 PPR Incremental Encoder Attached**
- **Totally Enclosed, Self-Cooled**
- **Power Ratings up to 1.0 kWatts**
- **Optional Brake and Oil Seal**
- **Long Life and Highly Reliable**
- **Neodymium-Iron-Boron Magnets (NdFeB)**
- **CE Certified**




DESCRIPTION

Anaheim Automation's Digital AC Servo Motors offer a simple solution to servo applications involving speed and positioning control. The AC EMJ-10 Servo Motor comes standard with a 2,500 Pulses Per Revolution (PPR) Incremental Encoder, runs at a maximum speed of 4,500 RPM, provides peak values up to 300% of the rated torque and current values, and has a rated torque of 450 oz-in with a 1.0 kWatt power rating. These enclosed and self-cooled motors also provide longer motor life and higher reliability. The EMJ-10 AC Servo Motors enable industrial motion control applications with medium inertia to attain a great combination of speed and positioning functionality.

SPECS


Model #	Rated Torque (oz-in)	Rated Power (Watts)	Rated Speed (rpm)	Max Speed (RPM)	Rated Current (A rms)	Max Current (A rms)	Brake (24VDC)	Inertia (oz-in-sec ²)	Electric Time Constant T _E (ms)	Back EMF Voltage K _E (V/krpm)	Torque Constant K _T (oz-in/A)	Resistance (ohms)	Weight (lbs)
EMJ-10APB22	450	1000	3000	4500	5.3	15.9	No	0.0246	9.9	38.4	86.8	1.6	9.93
EMJ-10APB24	450	1000	3000	4500	5.3	15.9	Yes	0.0265	9.9	38.4	86.8	1.6	15.06

TORQUE CURVE



A: Continuous Working Area
 B: Repeatedly Working Area

L010977




Note: All Dimensions in millimeters (mm)

Model #	L
EMJ-10APB22	156
EMJ-10APB24	199

Note: Part Number EMJ-10APB24 is with the brake option. The length of 'L' includes the motor body length + the length of the brake.

Encoder Connector Specification:


Plug
172169-1 (AMP)
170359-3 (AMP)



Pin No.	Signal	Color
1	A+	BLUE
2	B+	GREEN
3	C+	YELLOW
4	A-	BLUE/BLACK
5	B-	GREEN/BLACK
6	C-	YELLOW/BLACK
7	PG 5V	RED
8	PG 0V	BLACK
9	FG	SHIELD

Motor Connector Specification:


Plug
172167-1 (AMP)
170360-1 (AMP)



Pin No.	Signal	Color
1	U	RED
2	V	BLUE
3	W	WHITE
4	FG	GREEN/YELLOW

Brake Connector Specification:

Plug
172165-1 (AMP)
170360-1 (AMP)



Pin No.	Signal	Color
1	B1	WHITE
2	B2	BLUE

Power Requirement: 220VAC	Vibration: 49 m/s ²	Running Air Pressure: 86 to 106 kPa
Insulation Class: F	Ambient Temperature: 20% to 80% RH	Insulation Voltage Endurance: AC 1800C, 50Hz, 1 min
Ambient Temperature: 0°C to 40°C	IP Rating: IP65	Insulation Impedance: Not Less Than 50M Under Normal Conditions
Running Temperature: -25°C to 40°C	Running Humidity: Not More Than 90%, Under 25°C	

Compatible Driver

Part Number	Description
PRONET-E-10A	Servo Driver
ETS-1010APC-CAN	Servo Driver
ETS-101010APC-CAN	Servo Driver



Compatible Cables

Part Number	Description	Compatible Drivers
PDM-JB18-05	Power Cable	PRONET-E-10A
BMP-JB24-05	Encoder Cable	
PRONET-PSC-CC24-02	Comm. Cable	
PDM-JB18-05	Power Cable	ETS-1010APC-CAN ETS-101010APC-CAN
BMP-JB24-05	Encoder Cable	
PSC-CC24-05	Comm. Cable	

